

To complete the clause, select the appropriate wording from below. Highlighted text can be 'dragged and dropped' to save typing.

## **R10 RAINWATER DRAINAGE SYSTEMS**

### **605 INSTALLATION GENERALLY:**

#### **Fullflow Self Priming Syphonic Roof Drainage System.**

Fullflow manufacture a Self Priming syphonic roof drainage system which consists of Primaflow® Self Priming syphonic roof outlets and associated pipework.

Create a revised clause 605A and complete as follows. Consult Fullflow Group Ltd technical literature for details. As syphonic systems have to be designed to suit each individual application, using a computer aided design process, Fullflow Group Ltd provide a full design and specification service combined with a project management system to oversee the project from design to on-site completion and it is recommended that they are consulted early in the design process.

#### **605A INSTALLATION GENERALLY**

Discharge of rainwater: Complete, and without leakage or noise nuisance.

All Components must be procured within an ISO 9001 accredited approved suppliers procedure.

Electrolytic corrosion: Avoid contact between dissimilar metals where corrosion may occur.

Plastics and galvanized steel pipes: In accordance with current and relevant British and European standards.

#### **Protection:**

Fit purpose made temporary caps to prevent ingress of debris.

Fit access covers, cleaning eyes and blanking plates as the work proceeds.

**Fixings/ Fasteners:** As section R10/610